



Monobloc container ISO-20foot-1CC equipped with divisible showers for ladies/men as required

MOD. CONSI20-3+2D-U/D.1

- | | |
|--|---|
| <ul style="list-style-type: none"> a) Sturdy carrying structure of bent aluminum profiles (alloy 6082) welded in the joints to form a self-supporting monobloc shelter, complete with ISO corner blocks positioned according to ISO standards. b) Transportable with all systems compatible with ISO containers and/or with normal vehicles with appropriate anchoring. c) platforms and steps for access, made entirely of aluminum, removable from the structure. d) Stainless steel floor with non-slip adhesive strips on water-repellent multilayer wood panel. e) Electro Galvanized grates flush with the floor, on recessed stainless-steel drip pans. f) Partitions made of insulated aluminum panels and/or coated laminate, without retaining profiles, therefore perfectly able for disinfecting. g) External walls of sandwich panels with double aluminum sheet of 1mm thickness and a polyurethane insulation of 40mm. h) Exterior windows made of aluminum profiles and "polycarbonate glazing" and panic bars on the doors. i) Two different entrances for ladies and gentlemen. Separate technical room equipped with lockable aluminum door and ventilation. Internal sliding door for subdivision (or not) in two different areas. j) 2 awnings to cover the access area (on request). k) painting with selected RAL colors and finishing with first-class quality materials. | <ul style="list-style-type: none"> 1. External power supply 220 V (or 380 V) via protected CEE plug. 2. Internal electrical panel for external branches and distributions to various users, such as lighting and sockets with appropriate safety devices in accordance with applicable regulations. 3. Earthing system with connection and relative piles. 4. Separate room with appropriate dimensions, accessible from outside equipped with: industrial hot water boiler, plant control, various accessories, discharges and distributions. 5. Equipment of the module, which can be divided into two different areas (ladies, gentlemen): <ul style="list-style-type: none"> ➤ Gentlemen's area: 3 shower cubicles + 1 stainless steel sink with 4 taps, bathroom accessories, mirrors and various shelves. ➤ Ladies area: 2 shower cubicles + 1 stainless steel sink with two faucets, bathroom accessories, mirrors and various shelves. ➤ Partition: the entire room with 3 + 2 showers can also be used for single-user or can be split, as mentioned above, for gentlemen and ladies. 6. Hydraulic system with external connection, 160-liter industrial electric boiler, timed mixer taps, water drainage system, all with quick couplings and flexible piping. 7. 2 ceiling fans (roof hatch, one for each area) double acting (In/Out) with speed control (on request). 8. Pipes, flexible tanks and sewage treatment pump (on request for occasional applications) and external connection accessories for discharges |
|--|---|

Price: ex works Gruaro (Venice), Italy

1. MOD. CONSI20-3+2D-U/D.1 (with 3+2 showers and a.m. equipment): ... Euro/pcs _____ + VAT